

Flexi Wood A50

MUSIC & BROADCAST AND HI-FI & HOME CINEMA



Available Finishes

- 5 Wood Colours:
- Wenge
 - White
 - Nordik
 - Light Brown
 - Cherry

Packing Information

Each panel - 600 x 600 x 54 mm*
 Units per box - 8
 Box - 620 x 620 x 494 mm
 Box Gross Weight - 15,3 kg
 Box m³ - N/A Box ft³ - N/A

*Please notice that the dimensions of this panel have a tolerance of +/- 3 mms

FEATURES

Flexi Wood A50 is a panel dedicated to the control of medium and medium-low frequencies. It acts simultaneously as an absorber and a reflector, controlling excess energy in a room without compromising its ambience. This helps to create listening spaces with a natural, bright sound.

The panel's revolutionary design is further enhanced by the addition of a wood surface. Long known for its excellent acoustic properties, the wood also adds elegance and modernity to the panel, making it suitable for use in any type of space.

The Flexi Wood panel is available in two different thicknesses for use in different frequency ranges. Flexi Wood A50 is designed to perform to maximum effect between 400 and 1250 Hz.

APPLICATIONS

Listening Rooms, Home Theaters, Recording and Broadcast Studios, Post Production Studios, Performance Spaces, Rehearsal Rooms, Conference and Teleconference Rooms, Public Spaces, Auditoriums, etc.

TECHNICAL INFORMATION

Material: Polyurethane Foam and Wood

Fire Rating:

Foam: M1 (NF P 502-94 and NF P 502-95)

Euroclass F (ISO 11925-2:2010)

Wood: Euroclass E (ISO 11925-2:2010)

Product Classification: Euroclass E (ISO 11925-2:2010)

Installation: Vicoustic Flexi Glue

PERFORMANCE

